

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2015

Revision: 06.03.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **OTTOSEAL S 100**
- **Application of the substance / the mixture** *Silicone sealant*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Hermann Otto GmbH
 Krankenhausstraße 14
 D-83413 Fridolfing
 Tel.: 0049/(0)8684/908-0
 Fax.: 0049/(0)8684/908-539
- **Further information obtainable from:**
 Tel.: 0049- (0)8684- 908- 641 (-460)
 E-Mail: alois.parzinger@otto-chemie.de
- **1.4 Emergency telephone number:** Tel.: 0049- (0)89- 192 40 (emergency telephone no.)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified according to the CLP regulation.
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC** *not applicable*
- **Information concerning particular hazards for human and environment:**
The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** *Void*
- **Hazard pictograms** *Void*
- **Signal word** *Void*
- **Hazard statements** *Void*
- **Additional information:**
Ensure good ventilation during application and curing.
Contains the active agent biocide 4,5-dichloro-2-octyl-2H-isothiazol-3-one to protect against mould infestation
Keep out of the reach of children.
Avoid contact with skin.
Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
- **2.3 Other hazards**
During the application and curing process of the material chemicals are released as vapour (see item 11). Therefore ensure good ventilation or exhaustion if necessary.
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** *Polydimethylsiloxane, filler, auxiliaries and acetoxycrosslinker*
- **Dangerous components:**

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2015

Revision: 06.03.2015

Trade name: OTTOSEAL S 100

(Contd. of page 1)

CAS: 4253-34-3 methylsilanetriyl triacetate

< 2.5%

EINECS: 224-221-9  C R34;  Xn R22
R14 Skin Corr. 1B, H314; Eye Dam. 1, H318;  Acute Tox. 4, H302

CAS: 17865-07-5 Propyltriacetoxysilan (PTA)

< 2.5%

EINECS: 241-816-9  C R34
R14 Skin Corr. 1B, H314· **Additional information** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

see item 8: Personal protective equipment

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.· **Information about storage in one common storage facility:** Store away from foodstuffs.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2015

Revision: 06.03.2015

Trade name: OTTOSEAL S 100

(Contd. of page 2)

- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

CAS No.	Designation of material	%	Type	Value	Unit
Additional Occupational Exposure Limit Values for possible hazards during processing:					
64-19-7 acetic acid					
OEL Short-term value: 50 mg/m ³ , 20 ppm					
Long-term value: 25 mg/m ³ , 10 ppm					
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type ABEK according to standard EN 14387) is used.
- **Protection of hands:** Protective gloves.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
Natural rubber, NR
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	pasty
Colour:	According to product specification
Odour:	Pungent
Odour threshold:	Not determined.
- **Change in condition**

Melting point/Melting range:	undetermined
Boiling point/Boiling range:	undetermined
- **Flash point:** undetermined
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Density at 20 °C:** 1.02 g/cm³

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2015

Revision: 06.03.2015

Trade name: OTTOSEAL S 100

(Contd. of page 3)

- **Solubility in / Miscibility with Water:** Insoluble

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Avoid strong heating.
- **10.6 Hazardous decomposition products:**
Tests on representative products have shown that above temperatures of 150 °C small quantities of formaldehyde are split off.
see item 5.2

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:**
not irritating
Source: ECHA
Test in accordance with: OECD Guideline 404 (rabbit).
- **on the eye:**
not irritating
Source: ECHA
Test in accordance with: OECD Guideline 405 (rabbit).
- **Other information (about experimental toxicology):**
In curing the material splits off acetic acid as damp. This may cause irritating effects to skin, eyes or respiratory system.

SECTION 12: Ecological information

- **12.2 Persistence and degradability**
- **Other information:** Product is not biodegradable.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Observe local by-laws.
Already cured material can be disposed of with the domestic or commercial waste.
Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2015

Revision: 06.03.2015

Trade name: OTTOSEAL S 100

(Contd. of page 4)

- **Uncleaned packaging:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, ADN, IMDG, IATA** Void
- **14.2 UN proper shipping name**
- **ADR, ADN, IMDG, IATA** Void
- **14.3 Transport hazard class(es)**
- **ADR, ADN, IMDG, IATA**
- **Class** Void
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Not applicable.
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:** Not dangerous according to the above specifications.
- **UN "Model Regulation":** -

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Details of international registration status:**
Listed on or in accordance with the following inventories:

PICCS - Philippines	not listed
EINECS - Europe	listed
AICS - Australia	listed
DSL/NDL - Canada	listed
IECSC - China	listed
NZIoC - New Zealand	not listed
ECL/KECI - Korea	listed
TSCA - USA	listed
NECI - Taiwan	not listed
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.03.2015

Revision: 06.03.2015

Trade name: OTTOSEAL S 100

(Contd. of page 5)

*R14 Reacts violently with water.**R22 Harmful if swallowed.**R34 Causes burns.*

· **Department issuing MSDS:** Tel.: 0049- (0)8684- 908- 641

· **Contact:** Tel.: 0049- (0)8684- 908- 641 (-460)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

· *** Data compared to the previous version altered.**

GB