

USB Protector Head FH 240 / FH 240 TOP SK

Declaration of performance
Identification no.: 2400/2013/06/11

Highly breathable membrane
Riwega | eternitycomfort

1	Product Type: Unique identification code of the product-type	02050224 USB Protector Head FH 240 / 02020224 USB Protector Head FH 240 TOP SK	
2	Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	For batch number, please refer to the packaging	
3	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Breathable membrane for roof and wall	
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)	USB Protector Head FH 240 / USB Protector Head FH 240 TOP SK Riwega srl, 39044 Egna (BZ), Via Isola di Sopra 28	
5	Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	Not relevant	
6	System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V	System 3	
7	Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonized standard	EN 13984, System 3: Notified bodies have performed Initial Type Testing (ITT) according to System 3.	
8	Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued	Not relevant	
9	Declared performance		
Essential characteristics		Performance	Method
Roll width		50 m	EN 1848-2
Roll length		1,50 – 3,0 m (+1,0/-0,4%)	EN 1848-2
Areal mass		240 (±10g/m²)	EN 1849-2
Resistance to water penetration		W1	EN 1928 Method A
Air layer equivalent to the vapour passage [S _d value]		0,1 m	EN ISO 12572
Fire reaction		Class E	EN 13501-1
Tensile strength MD/CD*		390/290 N/50mm (±40N/50mm)	EN 12311-1
Elongation MD/CD*		30/50 % (±30%)	EN 12311-1
Resistance to tearing MD/CD*		300/400 N (±30N)	EN 12310-1
Temperature resistance		-40°C / +120°C	-
After artificial ageing			
Resistance to water penetration		npd**	EN 1928 Method A
Tensile strength MD/CD*		npd**	EN 12311-1
Elongation MD/CD*		npd**	EN 12311-1
*MD= Machine Direction; CD= Cross Direction; **npd= no performance determined			
10	Declaration		
	The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:		
	 Rizzi Werner	 Gamper Werner	Egna, 05/07/2021