

Air Coll

Single-sided butyl adhesive strip with plaster-ready surface
Riwega | eternitycomfort

Construction specification
of: 01/01/2016
Art. 75X 02203207 - 150X 02203215
Rev.04 of: 20/08/2021

Supply and installation of the Riwega AIR COLL adhesive band, available in the version 75 X (H75mm) and 150 X (H150mm), consisting of a 0.9 mm thick butyl base covered on the upper surface with a plasterable non-woven polypropylene fabric and protected in the lower part by a pre-cut liner in the central part to facilitate a quick and perfect installation around both corner and rounded interruptions, for water, air and wind tightness on:

- interruptions of Riwega's shields and breathable membranes due to the presence of roof windows, chimneys or other openings;
- cracks between wooden structures and masonry before the plaster is applied;
- joints for the installation of false frames on the exterior underside to ensure windtightness and watertightness, where there is a need to create a bend in the waterproofing material and/or the need to shave or plaster the surface.

Laying must be completed with strong pressure using a special roller to ensure that 100% of the adhesive base adheres perfectly to the surface to be sealed.

Supplier: Riwega Srl, via Isola di Sopra 28, 39044 Egna (BZ) - I

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.