

Tape 1 PE

Polyethylene adhesive tape coated with highly adhesive acrylic glue
Riwega | eternitycomfort

Technical data sheet
of 06/02/2014
Art. Nr. 02040160-02040193-02040194
Rev.09 of: 30/10/2022



Properties	Tape 1 PE	Tape 1 PE 100 X	Tape 1 PE 150
Article	02040160	02040193	02040194
Measurements	60 mm x 25 m	100 mm x 25 m	150 mm x 25 m
Colour	Blue		
Adhesive	Solvent and emollient free acrylic based adhesive		
Adhesive backing	LDPE-Film (70 µm)		
Adhesive weight	210 g/m ² (DIN EN ISO 536)		
Reinforcement	PET mesh		
Thickness (without cover)	0,27 - 0,29 mm (DIN EN 1942)		
Covering material	Silicone liner	Synthetic liner cut in half lengthwise	Silicone liner
Tear strength with elasticity	≥ 25 N/25mm; 300% (DIN EN 14410)		
Recommended application temperature	+5°C / +30°C (workable from -10°C)		
Operating temperature	-30°C / +100°C		
Sd value	approx. 12 m		
Resistance to detachment	Passed (DIN 4108-11)		
Resistance to condensation	Very high		
Resistance to aging	Very high		
Initial adhesion (tack)	Very high		
UV stability	24 months*		
Packaging	10 rolls	6 rolls	4 rolls
Storage	Cool and dry away from UV rays, max. 24 months		
Storage temperature	+18 °C / +25 °C		

* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.