

Tape Green

Single-sided adhesive tape in PE with acrylic glue and PET-scrim
Riwega | eternitycomfort

Art.
Rev.05

Technical data sheet
of 15/05/2014
02040161 - 020401616
of 15/05/2023



PROPERTIES	Tape Green 50 mm x 25 m	Tape Green 60 mm x 25 m
Article	02040161	020401616
Measurements	50 mm x 25 m	60 mm x 25 m
Colour	Green with black writing	
Adhesive	Pure Polyacrylate, free of solvents and plasticizers	
Adhesive backing	PE-Film (70 µm)	
Adhesive density	200 g/m ²	
Reinforcement	PET / PVA mesh	
Thickness (without liner)	0,28 mm	
Covering material	Silicone paper liner (90 g/m ²)	
Tear strenght with elasticity	≥ 22 N/10mm; 586 % (DIN EN 14410)	
Adhesive strength (AFERA 5001)	≥ 25 N/25mm	
Working temperature**	+5 °C / +30 °C	
Operating temperature	-40 °C / +80 °C	
Sd value	Approx. 40 m	
Resistance to detachment	Compliant (DIN 4108-11)	
Resistance to condensation	High	
Initial adhesion (<i>tack</i>)	High	
UV stability (Adhesive backing)	12 months*	
Packaging	12 rolls	10 rolls
Storage	Cool and dry away from UV rays, max. 24 months	
Storage temperature	+18 °C / +25 °C	

* referring to the Central Europe climate

** recommended temperatures. The tape can also be processed from -10°C, after checking the condition of the laying surface and making sure that the minimum temperature of the tape respects the storage temperature.

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com.
This data sheet replaces the previous copy.