

Tape ICE

Acrylic adhesive tape suitable at low temperatures
Riwega | eternitycomfort

Technical data sheet

of: 26/11/2019

Art. 02040165

Rev.02 of: 31/10/2022

Properties	
Measurements	60 mm x 25 m
Colour	Silver film with white writing
Adhesive	Polyacrylate-based dispersion adhesive, free of solvents and plasticizers
Adhesive backing	LDPE-Film (70 µm)
Adhesive density	200 g/m ² (DIN EN ISO 536)
Reinforcement	PET-mesh
Thickness (without liner)	0,26 - 0,28 mm (DIN EN 1942)
Covering material	Siliconized liner
Tear strength with elasticity	≥ 25 N/25 mm; 50% (DIN EN 14410)
Working temperature	+5 °C / +30 °C (workable from -20°C)
Operating temperature	-30 °C / +100 °C
Sd value	approx. 11 m
Resistance to detachment	Compliant (DIN 4108-11)
Resistance to condensation	Very high
Resistance to ageing	Very high
Initial adhesion (<i>tack</i>)	Very high
UV stability (Adhesive backing)	24 months*
Packaging	10 rolls
Storage	Store in the original and unopened packaging, in a dry and well ventilated place at a temperature between +18°C and +25°C, for max. 24 months



* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.