

Air Coll

Single-sided butyl adhesive strip with plaster-ready surface
Riwega | eternitycomfort

Technical data sheet
of: 06/02/2014
Art. 02203207 / 02203215
Rev.05 of: 13/08/2021

Properties	AIR Coll 75X	AIR Coll 150X
Article no.	Art.02203207	Art.02203215
Material	PP / butyl	
Liner	PE (divided in half)	
Measurements	75 mm x 25 m	150 mm x 25 m
Thickness	1 mm	
Colour	Grey	
Weight	approx.1,40 g/cm ³ (DIN EN ISO 1183-1)	
Application temperature	+5°C / +30°C	
Service temperature	-40°C / +100°C	
Hardness (Shore00)	approx.40 (DIN EN ISO 868)	
Viscosity	Stable (DIN EN ISO 7390)	
Ignition temperature	>400°C (DIN 51794)	
Compression resistance	>0,04 N/mm ² (DTU 39.4)	
Solid content	>99 % (DIN EN ISO 10563)	
Fire behavior	B2, normally flammable (DIN 4102)	
UV-stability	3 months*	
Emissions	Very low (according to Emissioncode®)	
Packaging	4 rolls	1 roll
Storage	Store in a dry place at approximately 20°C, out of direct sunlight for a maximum of 12 months	

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.